NUMBER OF TEETH	40
NUMBER OF THREADS	1
DIAMETRAL PITCH	22,57778
DIAMETRAL PITCH NORMAL	22,60309
MODULE	1,12500
MODULE NORMAL	1,12374
PRESSURE ANGLE	20,02064deg
PRESSURE ANGLE NORMAL	20,00000deg
PITCH DIAMETER, GEAR	45,000mm
PITCH DIAMETER, WORM	23,750mm
LEAD GEAR	3,534mm
LEAD WORM	3,534mm
LEAD WORM ANGLE	2,71198deg
ADDENDUM GEAR	1,125mm
ADDENDUM WORM	1,125mm
DEDENDUM GEAR	1,406mm
DEDENDUM WORM	1,406mm
WHOLE DEPTH	2,531mm
ADDENDUM MODIFICATION	
ADD. MOD. COEFFICIENT	
DIRECTION GEAR	Right_Hand
LEAD GEAR	3,534mm
LEAD WORM	3,534mm
LEAD WORM ANGLE	2,71198deg
WORM OUTSIDE DIAMETER	26,000
CONTACT RATIO	1,846
BACKLASH GEAR	0,000mm
BACKLASH WORM	0,000mm
CROWNING DROP	0,000mm
TOOTH THICKNESS GEAR	1,7671mm
TOOTH THICKNESS WORM	1,7671mm





СЕЧЕНИЕ А-А

1.H14,h14 ±t2/2

Сопрягаемая деталь: Червяк М1125

ПО УМОЛЧАНИЮ: РАЗМЕРЫ В МИЛЛИМЕТРАХ ШЕРОХОВАТОСТЬ: ДОПУСКИ: ЛИНЕЙНЫЕ: УГЛОВЫЕ:		ОБРАБОТКА:		СГЛАДИТЬ ЗАУСЕНЦЫ И ОСТРЫЕ КРОМКИ	НЕ МАСШТАБИРОВАТЬ ЧЕРТЕЖ	РЕДАКЦИЯ	
	ИМЯ	ПОДПИСЬ	ДАТА		НАЗВАНИЕ:		
Разраб.					Колесо Z40		
Пров.							
Утв.							
Маш.							
Т.контр				МАТЕРИАЛ: БР010Ф1	ЧЕРТЕЖ №:		А4
				МАССА:	МАСШТАБ:1:1	ЛИСТ 1 ИЗ 1	