



1	2	3	4	5	6																																																																																										
<table><tr><td>NUMBER OF TEETH</td><td>40</td></tr><tr><td>NUMBER OF THREADS</td><td>1</td></tr><tr><td>DIAMETRAL PITCH</td><td>22,57778</td></tr><tr><td>DIAMETRAL PITCH NORMAL</td><td>22,60309</td></tr><tr><td>MODULE</td><td>1,12500</td></tr><tr><td>MODULE NORMAL</td><td>1,12374</td></tr><tr><td>PRESSURE ANGLE</td><td>20,02064deg</td></tr><tr><td>PRESSURE ANGLE NORMAL</td><td>20,00000deg</td></tr><tr><td>PITCH DIAMETER, GEAR</td><td>45,000mm</td></tr><tr><td>PITCH DIAMETER, WORM</td><td>23,750mm</td></tr><tr><td>LEAD GEAR</td><td>3,534mm</td></tr><tr><td>LEAD WORM</td><td>3,534mm</td></tr><tr><td>LEAD WORM ANGLE</td><td>2,71198deg</td></tr><tr><td>ADDENDUM GEAR</td><td>1,125mm</td></tr><tr><td>ADDENDUM WORM</td><td>1,125mm</td></tr><tr><td>DEDENDUM GEAR</td><td>1,406mm</td></tr><tr><td>DEDENDUM WORM</td><td>1,406mm</td></tr><tr><td>FILLET RADIUS</td><td>0,337mm</td></tr><tr><td>WHOLE DEPTH</td><td>2,531mm</td></tr><tr><td>ADDENDUM MODIFICATION</td><td></td></tr><tr><td>ADD. MOD. COEFFICIENT</td><td></td></tr><tr><td>DIRECTION GEAR</td><td>Right Hand</td></tr><tr><td>LEAD GEAR</td><td>3,534mm</td></tr><tr><td>LEAD WORM</td><td>3,534mm</td></tr><tr><td>LEAD WORM ANGLE</td><td>2,71198deg</td></tr><tr><td>WORM OUTSIDE DIAMETER</td><td>26,000</td></tr><tr><td>GEAR OUTSIDE DIAMETER</td><td>48,421mm</td></tr><tr><td>CONTACT RATIO</td><td>1,846</td></tr><tr><td>LENGTH WORM</td><td>25,000mm</td></tr><tr><td>FACE WIDTH GEAR</td><td>14,000mm</td></tr><tr><td>BACKLASH GEAR</td><td>0,000mm</td></tr><tr><td>BACKLASH WORM</td><td>0,000mm</td></tr><tr><td>CROWNING DROP</td><td>0,000mm</td></tr><tr><td>TOOTH THICKNESS GEAR</td><td>1,7671mm</td></tr><tr><td>TOOTH THICKNESS WORM</td><td>1,7671mm</td></tr><tr><td>CENTER DISTANCE</td><td>34,375mm</td></tr></table>						NUMBER OF TEETH	40	NUMBER OF THREADS	1	DIAMETRAL PITCH	22,57778	DIAMETRAL PITCH NORMAL	22,60309	MODULE	1,12500	MODULE NORMAL	1,12374	PRESSURE ANGLE	20,02064deg	PRESSURE ANGLE NORMAL	20,00000deg	PITCH DIAMETER, GEAR	45,000mm	PITCH DIAMETER, WORM	23,750mm	LEAD GEAR	3,534mm	LEAD WORM	3,534mm	LEAD WORM ANGLE	2,71198deg	ADDENDUM GEAR	1,125mm	ADDENDUM WORM	1,125mm	DEDENDUM GEAR	1,406mm	DEDENDUM WORM	1,406mm	FILLET RADIUS	0,337mm	WHOLE DEPTH	2,531mm	ADDENDUM MODIFICATION		ADD. MOD. COEFFICIENT		DIRECTION GEAR	Right Hand	LEAD GEAR	3,534mm	LEAD WORM	3,534mm	LEAD WORM ANGLE	2,71198deg	WORM OUTSIDE DIAMETER	26,000	GEAR OUTSIDE DIAMETER	48,421mm	CONTACT RATIO	1,846	LENGTH WORM	25,000mm	FACE WIDTH GEAR	14,000mm	BACKLASH GEAR	0,000mm	BACKLASH WORM	0,000mm	CROWNING DROP	0,000mm	TOOTH THICKNESS GEAR	1,7671mm	TOOTH THICKNESS WORM	1,7671mm	CENTER DISTANCE	34,375mm																		
NUMBER OF TEETH	40																																																																																														
NUMBER OF THREADS	1																																																																																														
DIAMETRAL PITCH	22,57778																																																																																														
DIAMETRAL PITCH NORMAL	22,60309																																																																																														
MODULE	1,12500																																																																																														
MODULE NORMAL	1,12374																																																																																														
PRESSURE ANGLE	20,02064deg																																																																																														
PRESSURE ANGLE NORMAL	20,00000deg																																																																																														
PITCH DIAMETER, GEAR	45,000mm																																																																																														
PITCH DIAMETER, WORM	23,750mm																																																																																														
LEAD GEAR	3,534mm																																																																																														
LEAD WORM	3,534mm																																																																																														
LEAD WORM ANGLE	2,71198deg																																																																																														
ADDENDUM GEAR	1,125mm																																																																																														
ADDENDUM WORM	1,125mm																																																																																														
DEDENDUM GEAR	1,406mm																																																																																														
DEDENDUM WORM	1,406mm																																																																																														
FILLET RADIUS	0,337mm																																																																																														
WHOLE DEPTH	2,531mm																																																																																														
ADDENDUM MODIFICATION																																																																																															
ADD. MOD. COEFFICIENT																																																																																															
DIRECTION GEAR	Right Hand																																																																																														
LEAD GEAR	3,534mm																																																																																														
LEAD WORM	3,534mm																																																																																														
LEAD WORM ANGLE	2,71198deg																																																																																														
WORM OUTSIDE DIAMETER	26,000																																																																																														
GEAR OUTSIDE DIAMETER	48,421mm																																																																																														
CONTACT RATIO	1,846																																																																																														
LENGTH WORM	25,000mm																																																																																														
FACE WIDTH GEAR	14,000mm																																																																																														
BACKLASH GEAR	0,000mm																																																																																														
BACKLASH WORM	0,000mm																																																																																														
CROWNING DROP	0,000mm																																																																																														
TOOTH THICKNESS GEAR	1,7671mm																																																																																														
TOOTH THICKNESS WORM	1,7671mm																																																																																														
CENTER DISTANCE	34,375mm																																																																																														
<div><div></div><div></div></div> <div><div>Сопрягаемая деталь: Колесо Z40</div><div><div>1. 300...350 НВ</div><div>2. H14,h14 ±t2/2</div><div>3. Покрытие Хим. Окс. прм.</div></div></div>																																																																																															
<table><tr><td colspan="2">ПО УМОЛЧАНИЮ: РАЗМЕРЫ В МИЛЛИМЕТРАХ ШЕРОХОВАТОСТЬ: ДОПУСКИ: ЛИНЕЙНЫЕ: УГЛОВЫЕ:</td><td colspan="2">ОБРАБОТКА:</td><td colspan="2">СГЛАДИТЬ ЗАУСЕНЦЫ И ОСТРЫЕ КРОМКИ</td><td colspan="2">НЕ МАСШТАБИРОВАТЬ ЧЕРТЕЖ</td><td colspan="2">РЕДАКЦИЯ</td></tr><tr><td colspan="2">ИМЯ</td><td colspan="2">ПОДПИСЬ</td><td colspan="2">ДАТА</td><td colspan="2">НАЗВАНИЕ:</td><td colspan="2"></td></tr><tr><td colspan="2">Разраб.</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">Червяк</td><td colspan="2"></td></tr><tr><td colspan="2">Пров.</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">Утв.</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">Маш.</td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2">Т.контр</td><td colspan="2"></td><td colspan="2"></td><td colspan="2">МАТЕРИАЛ: Ст40X</td><td colspan="2">ЧЕРТЕЖ №:</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">МАССА:</td><td colspan="2">МАСШТАБ:2:1</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2">ЛИСТ 1 ИЗ 1</td></tr></table>						ПО УМОЛЧАНИЮ: РАЗМЕРЫ В МИЛЛИМЕТРАХ ШЕРОХОВАТОСТЬ: ДОПУСКИ: ЛИНЕЙНЫЕ: УГЛОВЫЕ:		ОБРАБОТКА:		СГЛАДИТЬ ЗАУСЕНЦЫ И ОСТРЫЕ КРОМКИ		НЕ МАСШТАБИРОВАТЬ ЧЕРТЕЖ		РЕДАКЦИЯ		ИМЯ		ПОДПИСЬ		ДАТА		НАЗВАНИЕ:				Разраб.						Червяк				Пров.										Утв.										Маш.										Т.контр						МАТЕРИАЛ: Ст40X		ЧЕРТЕЖ №:								МАССА:		МАСШТАБ:2:1										ЛИСТ 1 ИЗ 1	
ПО УМОЛЧАНИЮ: РАЗМЕРЫ В МИЛЛИМЕТРАХ ШЕРОХОВАТОСТЬ: ДОПУСКИ: ЛИНЕЙНЫЕ: УГЛОВЫЕ:		ОБРАБОТКА:		СГЛАДИТЬ ЗАУСЕНЦЫ И ОСТРЫЕ КРОМКИ		НЕ МАСШТАБИРОВАТЬ ЧЕРТЕЖ		РЕДАКЦИЯ																																																																																							
ИМЯ		ПОДПИСЬ		ДАТА		НАЗВАНИЕ:																																																																																									
Разраб.						Червяк																																																																																									
Пров.																																																																																															
Утв.																																																																																															
Маш.																																																																																															
Т.контр						МАТЕРИАЛ: Ст40X		ЧЕРТЕЖ №:																																																																																							
						МАССА:		МАСШТАБ:2:1																																																																																							
								ЛИСТ 1 ИЗ 1																																																																																							
1	2																																																																																														